


IDROPULITRICE AD ACQUA CALDA 2 POLI (2800 giri/min) HOT WATER HIGH PRESSURE WASHER 2 POLES (2800 giri/min)

Caratteristiche

- Regolazione del bruciatore, combustione ottimizzata.
- Motore ausiliario per ventilazione caldaia.
- Pompa assiale, testata in alluminio a tre pistoni in acciaio ad alta resistenza.
- Caldaia verticale con serpentina in acciaio ad alto rendimento.
- Valvola di sicurezza.
- Regolazione automatica della temperatura.
- Manico con impugnatura ergonomica completo di serbatoio detergente e portaccessori
- Sistema Automatic Stop.
- Aspirazione detergente diretta dal serbatoio

Features

- Adjustable burner for an optimized combustion
- Auxiliary motor for ventilation of hot water heater
- Vertical hot water heater with a high efficiency steel winding
- Security valve
- Automatic temperature regulation
- Ergonomic handle complete with detergent tank and accessory holder
- Automatic stop system
- Direct suction of detergent from the tank

Pressione operativa Operative pressure	110/145 bar			
Voltage / Frequency	V 230-50 Hz			
Temperatura / Temperature	90° C			
Portata max. / Delivery max. (l/1')	8			
N° giri 1' / r.p.m.	2800			
Potenza / Power (watt)	2300			
Peso / Weight (Kg)	43			
Imballo Packaging (mm)		L 630	P 430	H 730



Accessori inclusi - Standard accessories

Pistola, lancia e tubo professionale 8mt
Gun, lance and professional hose 8mt



IDROPULTRICE AD ACQUA CALDA 2 POLI (2800 giri/min) HOT WATER HIGH PRESSURE WASHER 2 POLES (2800 giri/min)

Caratteristiche

- Motore ausiliario per ventilazione gruppo caldaia
- Pompa assiale con testata in ottone a tre pistoni in acciaio ceramicato e valvola di by-pass incorporata
- Valvole di aspirazione e mandata in acciaio inox
- Caldaia verticale con serpentina in acciaio ad alto rendimento termico
- Regolatore della temperatura
- Pompa del gasolio con valvola by-pass di scarico
- Serbatoio detergente integrato (2,5 litri) per aspirazione indiretta
- Serbatoio del gasolio (14 litri)
- Regolatore di pressione
- Manometro in bagno di glicerina
- Alloggiamento tubo
- Supporto porta accessori
- Impugnatura ergonomica.

Features

- Auxiliary motor for ventilation boiler group
- Axial pump in ceramic steel with a three piston brass head and built-in bypass valve
- Stainless steel suction valve and delivery
- Vertical hot water heater with a high efficiency steel winding
- Temperature regulator
- Diesel pump with bypass exhaust valve
- Built-in detergent tank (2,5 liters) for indirect suction
- Diesel tank (14 liters)
- Pressure regulator
- Glycerin bath pressure gauge
- Cable housing
- Accessory holder
- Ergonomic handle


Accessori inclusi - Standard accessories

Pistola, lancia e tubo professionale 8mt
Gun, lance and professional hose 8mt



Lance 700mm



Pressione operativa Operative pressure	130/150 bar			
Voltage / Frequency	V 230-50 Hz			
Temperatura / Temperature	90° C			
Portata max. / Delivery max. (l/1')	10			
N° giri 1' / r.p.m.	2800			
Potenza / Power (watt)	3000			
Peso / Weight (Kg)	55			
Imballo Packaging (mm)		L 820	P 600	H 870



VAPO 10/130