



SEPARATORE SC-3500

ITA-ING



SEPARATORE SC-3500

ITA Centrifuga verticale per la chiarificazione dell'olio mediante l'eliminazione di eventuali particelle solide e goccioline d'acqua. Il separatore è dotato di un sistema elettronico per l'avvio ed il controllo della velocità, di una colonna con un numero elevato di dischi di varie dimensioni per la separazione delle fasi e di un sistema automatico di scarico dei fanghi. Questa centrifuga ad alto numero di giri è realizzata secondo le normative CE e internazionali sia nella scelta dei materiali che nella costruzione. L'olio in uscita dal separatore è pronto per lo stoccaggio o eventuale filtrazione.

ENG Vertical centrifuge for the olive oil clarification by the elimination of the eventual solid particles and water droplets. The separator is equipped with an electronic system for the starting and the speed control, and a column with a great number of variable thickness stainless steel disks for the phases separation and an automatic sludge discharge system. This high speed rotating centrifuge is made according to the EC and international standards for both the material choice and the construction. The output oil from the separator is ready for the storage or the filtration.



CARATTERISTICHE TECNICHE

	PESO TAMBURO (Kg) DRUM WEIGHT (Kgs)	PESO SEPARATORE (Kg) SEPARATOR WEIGHT (Kgs)	VELOCITA' (RPM) SPEED (RPM)	POTENZA (kW) POWER REQUIREMENTS (kW)	CAPACITA' IDRAULICA (Lt/h) HYDRAULIC CAPACITY (Lt/h)
SC-3500	140	1050	6800	7,5	3500

